

Class 250 Iron Body Automatic Stop Check Valves

Bolted Bonnet • Angle Pattern • Renewable Seat and Disc* • Bronze Mounted

250 PSI/17.2 Bar Saturated Steam to 406° F/207° C
500 PSI/34.5 Bar Non-Shock Cold Working Pressure
to -20° F to 150° F/-29° C to 66° C ♦

CONFORMS TO MSS SP-85

MATERIAL LIST

PART	SPECIFICATION
1. Handwheel Nut	Steel ASTM A307
2. Identification Plate	Aluminum
3. Handwheel	Cast Iron ASTM A126 Class B
4. Stem	Brass ASTM B 16 Alloy C36000
5. Yoke Bushing	Cast Bronze ASTM B584 Alloy C84400
6. Bonnet	Cast Iron ASTM A126 Class B
7. Gland Follower Stud	Steel ASTM A307 (not shown)
8. Gland Follower Nut	Brass ASTM F467 Alloy C27000 (not shown)
9. Gland Follower	Ductile Iron ASTM A536
10. Packing Gland	Zinc Plated Powdered Iron ASTM B783 or Brass ASTM B16
11. Packing	PTFE Braided
12. ¹ Butterfly Handle Nut	Steel ASTM A307
13. ¹ Butterfly Handle	Cast bronze ASTM B584 Alloy C84400
14. ¹ Control Valve Stem	Bronze ASTM B371 Alloy C69400
15. ¹ Control Valve Pack Nut	Cast Bronze ASTM B584 Alloy C84400
16. ¹ Control Valve Pack Gland	Brass ASTM B16 Alloy C36000
17. ¹ Control Valve Packing	Synthetic Fibers with Graphite
18. ¹ Control Valve Body	Cast Bronze ASTM B584 Alloy C84400
19. Hex Head Cap Screw	Steel ASTM A307
20. Body Gasket	Reinforced Graphite
21. ¹ Dashpot Gasket	Reinforced Graphite
22. ¹ Dashpot	Cast Bronze ASTM B584 Alloy C84400
23. ¹ Piston-Disc	Cast Iron ASTM A126 Class B
24. ¹ Piston Ring (2)	PTFE Composite Material
25. ¹ Disc Face Ring	Cast Bronze ASTM B584 Alloy C84400
26. ¹ Seat Ring	Cast Bronze ASTM B584 Alloy C84400
27. Body	Cast Iron ASTM A126 Class B
28. ² Piston Ring Collar	Brass ASTM B16 Alloy C36000
29. ² Disc Cage	Bronze ASTM B584 Alloy C84400
30. ² PTFE Disc	PTFE
31. ² Disc Plate and Nut	Bronze ASTM B584 C84400
32. ² Piston Rod Plug	Brass ASTM B16 Alloy C36000
33. ² Piston Rod Plug Pin	Red Bronze ASTM B 140 Alloy C31400

¹ 4" thru 8" size only. (4" thru 8" have Cast Iron Disc with Bronze Disc Face Ring)

² TFE Seat Disc in 2½" and 3" only. Maximum 150 psi saturated steam working pressure

DIMENSIONS—WEIGHTS—QUANTITIES

Dimensions												
Size	A	B	C	D	E	Weight						
In. mm.	In. mm.	In. mm.	In. mm.	In. mm.	In. mm.	Lbs.	Kg.					
2½ 65	5.75 146	12.63 321	8 203	7.50 191	1.00 25	80	36					
3 80	6.25 159	14.00 356	10 254	8.25 210	1.13 29	102	46					
4 100	7.00 178	16.50 419	10 254	10.00 254	1.25 32	168	76					
6 150	8.75 222	20.75 527	14 356	12.50 318	1.44 37	311	141					
8 200	10.50 267	23.81 605	16 406	15.00 381	1.63 41	520	236					

* With proper machining facilities available.

Valve must be installed vertically.

VISIT WWW.NIBCO.COM FOR CURRENT CHEM-GUIDE AND GALVANIC POTENTIAL IN PIPING SYSTEMS INFORMATION.


Visit our website for the most current information.

♦ For detailed Operating Pressure, refer to Pressure Temperature Chart on page 114.




F-869-B

Flanged
Series D



F-869-B

Flg x Flg



Freezing Weather Precaution – Subsequent to testing a piping system, valves should be in an open position to allow complete drainage.